

BONATITAN DGD

Dikey Tip Soğutucu Reyonu
Vertical Type Cooler Cabinet




TEKNİK DETAYLAR

Technical Details


Dikey Tip Soğutucu Reyonu
Vertical Type Cooler Cabinet

BONATITAN DGD


OUR DESIGN
INDUSTRIAL COOLING SYSTEMS




BONATITAN DGD 750/H2200




BONATITAN DGD 750/H2050




BONATITAN DGD 900/H2200




BONATITAN DGD 900/H2050




BONATITAN DGD 1000/H2200




BONATITAN DGD 1000/H2050




BONATITAN DGD 1100/H2200




BONATITAN DGD 1100/H2050




BONATITAN MT DGD 750/H2200




BONATITAN MT DGD 750/H2050




BONATITAN MT DGD 900/H2200




BONATITAN MT DGD 900/H2050




BONATITAN MT DGD 1000/H2200



BONATITAN MT DGD 1000/H2050



BONATITAN MT DGD 1100/H2200



BONATITAN MT DGD 1100/H2050

Available Modules / Kullanılabilir Modüller

Length/Uzunluk (mm)	1250	1875	2500	2812	3125	3750	Gondola / Head
Side panel/ Yan kapak (mm)	40	40	40	40	40	40	40

Operating Temperatures / Çalışma Sıcaklıkları

DP	MT	FV
M2 (-1/+7°C)	M1 (-1/+5°C)	H1 (+1/+10°C)

Ambient Conditions Ortam Koşulları

25°C / 60% RH
(EN ISO 23953-2)



SÜTLÜK / DAIRY PRODUCTS

PAKET ET & MEYVE VE SEBZE
PACKED MEAT & FRUITS VEGETABLES